



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **07134947 A**(43) Date of publication of application: **23.05.95**

(51) Int. Cl.

H01J 17/04**H01J 17/49**(21) Application number: **05283446**(22) Date of filing: **12.11.93**(71) Applicant: **MATSUSHITA ELECTRON CORP**(72) Inventor: **MAE HAJIME
HIRAO KAZUNORI
WAKITANI TAKAO**(54) **GAS DISCHARGE DISPLAY APPARATUS**

(57) Abstract:

PURPOSE: To prolong the life of a gas discharge display apparatus without degrading the insulating property of a dielectric layer surface by arranging an auxiliary discharging electrode to charge a second dielectric layer and a second electrode opposite to each other and forming the second dielectric layer out of porous material.

CONSTITUTION: An auxiliary discharging electrode 2, a first dielectric layer 3a, a second dielectric layer 3b, and stripe shape first electrode 4 group are successively layered on a glass substrate 1. Stripe shape second electrode 6 group which are kept from the first electrode 4 group by a prescribed distance by a barrier plate 5 and rectangular to the electrode 4 group are formed on a translucent glass substrate 7 and the discharging electrode 2 and an electrode 6 are so set on the opposite to each other as to charge the dielectric layer 3b. The dielectric layer 3a is formed out of a compound material containing oxides and having a prescribed pore diameter. The dielectric layer 3b is formed out of a porous compound material having a prescribed pore diameter. The lower face of the

barrier plate 5 touches the dielectric layer 3b and the electrode 4 group and the upper face of the barrier plate 5 touches the glass substrate 7 and each contact part of the substrate 1 and the substrate 7 is air-tightly sealed with low melting glass and thus discharge spaces are formed.

COPYRIGHT: (C)1995,JPO

